Tandem RiteTouch Hybrid Wash System

Friction hybrid!



Quality clean and unique wash experience!



Vehicle Wash Systems


A DOVER COMPANY

www.pdqinc.com

What is RiteTouch?

PDQ has done it again – we have pioneered a new industry defining vehicle cleaning method with the *Tandem* RiteTouch RT300*. This superior hybrid carwash system is the integration of both touch-free and friction cleaning methods, giving operators a new choice from the market leader – **PDQ**.

Innovation



Quality Clean

Duallies, open bed pick-ups, SUV's, standard vehicles – all get a high quality clean in the **Tandem® RiteTouch.**A combination of hybrid technology offers both friction and touch-free washing. No other friction type machine can offer powerful top blasters, bug prep or triplex wheel cleaning system for a completely clean vehicle.

Tandem® offers the widest top brush spanning 86 inches in length. Large SUV's and trucks are typically 75 inches in width. The unique side profiling brush adjusts based on the position of the vehicle and effectively removes stubborn soil from the vehicle's surface.


Wash Experience

Virtual Treadle® – eliminates drive-on floor steel to create a consumer friendly experience AND speed through-put. Completely retractable top and side brush - creates a completely open bay appearance for consumers AND reduces the potential for damage within the bay.

Reduced noise and motion – consumers equate loud slapping noises and rocking of their vehicle with potential damage. Tandem[®] has significantly reduced both of these concerns compared to competitive equipment.

Tandem RiteTouch reduces overall brush time on the vehicle by 70% while producing a superior clean compared to traditional five brush systems. This means lower brush replacement costs!

Horizontal = time top brush contacts vehicle Vertical = accumulated seconds side brushes contact



Profitability

With fewer moving parts, Tandem® significantly reduces downtime and offers the most profitable value-added, up-selling options available to create a unique point of differentiation from your competition! Tandem® offers 3x foam, triplex wheel cleaning system, open truck bed sensor/top blasters, super sealant, virtual treadle, FlashDry, undercarriage, customizable brush colors – all designed to increase your profitability.

In fact, Tandem's basic wash with FlashDry™ is complete in just **2 minutes 15 seconds!***

That's the Tandem® Difference...

Two Bridges + Two Brushes + Two Cleaning Technologies = One Amazing Clean!

lechnologies = Une Amazing Clean!			
	Tandem"	Competitor 1	Competitor 2
Eliminates drive on floor steel	✓ Yes	no	no
Completely retracted top brush	✓ Yes	no	no
Completely retracted side brush	✓ Yes	no	no
Visually appealing	✓ Yes	no	no
Comfortable, quiet, virtually non-detectible wash motion by consumers	✓ Yes	no	no
Offers integrated FlashDry,™ Wheel Scrubbers, and Top Blasters	✓ Yes	no	no
Extended brush life and lower replacement cost	✓ Yes	no	no
3x Foam	✓ Yes	no	no
Super sealant ready	✓ Yes	no	no
*Wash times vary by individual wash conditions, machine package configurations, and ted	hnical experience.		

Tandem RiteTouch Hybrid Wash System

Common Feature Package, Perfectly Priced!

SUPER	Base machine with foam side brush and foam top brush Ultimate bridge cover package including full front and back covers for each bridge Front vehicle chemical applicator Bug prep Low-pressure drive-thru under carriage High-pressure side blaster with advanced wheel scrubber	 Super sealant ready 3x foaming conditioner applicators Clear coat protectant Spot-free intake kit Bay control box with conductor LED entrance & service confirmation signs High-pressure top blasters
DELUXE	Super Package - Add 4 Nozzle on-board MaxAir™ Fla	ashDry™ Dryer
ULTIMATE	Deluxe Package - Add Access® N-Series Customer N	Nanagement System

Other packages available, ask for details.

Building Requirements	Preferred	Minimum	
Bay Length w/On-Board or No Dryer	36' (10.97m)	30' (9.14 m)	
w/MaxAir Stand-Alone Dryer (with covers)	50' (15.24m)	39' 3" (11.96 m)	
Bay Width -Wall Mount	16' (4.8 m)	13' 6" (4.11 m)	
Freestanding Frame	16' (4.8 m)	13' 6" (4.11 m)	
Bay Height	11' (3.35 m)	10' 6" (3.20 m)	
Recommended Water Supply: Air Requirements:	30 GPM @ 20 psi On site Air Compressor is required. 1.5 SCFM at 10 PSI minimum, 90 PSI maximum		
Electrical Specifications	RT300)	
3 Separate Electrical Supplies are required for Wash Front Bridge Back Bridge Bay Box	208/23	30 V. 3 Ph 60 Hz @ 14 Amps 30 V. 3 Ph 60 Hz @ 32 Amps Single Ph 60 Hz @ 3 Amps	



Front Bridge
Back Bridge
Back Bridge
Bay Box

2 Separate Electrical Supplies are required for On-Board Dryers
#1

208/230 V. 3 Ph 60 Hz @ 14 Amps
208/230 V. 3 Ph 60 Hz @ 32 Amps
220 V. Single Ph 60 Hz @ 3 Amps
208/230 V. 3 Ph. 60 Hz @ 44 Amps

208/230 V. 3 Ph. 60 Hz @ 44 Amps 208/230 V. 3 Ph. 60 Hz @ 44 Amps





Please visit our website for **FREE** literature and DVD's on all our equipment!

www.pdqinc.com



A DOVER COMPANY